



# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 31-01-2014

Revision date:

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Oil Painting Medium Quick Drying  
Product code : 1108  
Type of product : Solvents  
Product group : Blend

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : Medium  
Function or use category : Solvents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664  
Nijendal 36  
3972 KC Driebergen Rijsenburg - Nederland  
T 0031 343 518 224 - F 0031 343 516 342  
[info@oldholland.com](mailto:info@oldholland.com) - [www.oldholland.com](http://www.oldholland.com)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
STOT SE 3 H336  
Asp. Tox. 1 H304  
Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

##### Classification according to Directive 67/548/EEC or 1999/45/EC

Xn; R65  
N; R51/53  
R10  
R66  
R67

Full text of R-phrases: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

Portugese Gum Turpentine

Hazard statements (CLP) :

H226 - Flammable liquid and vapour  
H302+H332 - Harmful if swallowed or if inhaled  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P261 - Avoid breathing vapours, mist, spray  
P273 - Avoid release to the environment  
P301+P310 - IF SWALLOWED: Immediately call a doctor  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P331 - Do NOT induce vomiting

EUH phrases :

EUH066 - Repeated exposure may cause skin dryness or cracking

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
Portugese Gum Turpentine	(CAS No) 8006-64-2 (EC no) 232-350-7 (EC index no) 650-002-00-6	50 - 75	Xn; R65 N; R51/53 R10 R66 R67
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)	(EC no) 919-446-0 (REACH-no) 01-2119458049-33	0 - 50	Xn; R65 N; R51/53 R10 R66 R67

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Portugese Gum Turpentine	(CAS No) 8006-64-2 (EC no) 232-350-7 (EC index no) 650-002-00-6	50 - 75	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)	(EC no) 919-446-0 (REACH-no) 01-2119458049-33	0 - 50	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of R- and H-phrases: see section 16

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Repeated exposure may cause skin dryness or cracking. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause an allergic skin reaction. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	--

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing vapors, mist, spray.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	--

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No naked lights. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, mist, spray.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Explosion-free electrical equipment and lighting with earth.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Solvent.


## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

Personal protective equipment : Gloves. Dust/aerosol mask. Safety glasses. Avoid all unnecessary exposure. Protective clothing.



Hand protection : Wear protective gloves. Since the product consists of several substances, it is possible to estimate the durability of the glove material beforehand and it therefore needs to be tested before use. Gloves must be replaced after each use and whenever signs of wear or perforation appear.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Colourless.

Odour : characteristic.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Self ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapour

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Relative density : No data available

Solubility : No data available

Log Pow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidising properties : No data available

Explosive limits : No data available

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established. Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful if inhaled.

Oil Painting Medium Quick Drying	
ATE (oral)	500,000 mg/kg bodyweight
ATE (dust,mist)	1,500 mg/l/4h

Portugese Gum Turpentine (8006-64-2)	
LD50 oral rat	5,76 mg/m <sup>3</sup>
ATE (oral)	500,000 mg/kg bodyweight
ATE (dermal)	1100,000 mg/kg bodyweight
ATE (dust,mist)	1,500 mg/l/4h

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 4 mg/kg

Skin corrosion/irritation	: Causes skin irritation. Repeated exposure may cause skin dryness or cracking
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Harmful if swallowed. Harmful if inhaled.
Other information	: Risk of aspiration pneumonia.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Portugese Gum Turpentine (8006-64-2)	
EC50 Daphnia 1	14,1 mg/l

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)

EC50 Daphnia 1	7,8 g/l
EC50 other aquatic organisms 1	3,59 g/l

### 12.2. Persistence and degradability

#### Oil Painting Medium Quick Drying

Persistence and degradability : May cause long-term adverse effects in the environment.

#### Portugese Gum Turpentine (8006-64-2)

Persistence and degradability : May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

#### Oil Painting Medium Quick Drying

Bioaccumulative potential : Not established.

#### Portugese Gum Turpentine (8006-64-2)

Bioaccumulative potential : Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

: Avoid release to the environment

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to an authorized waste treatment plant.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No (ADR)	: 1263
UN-No.(IATA)	: 1263
UN-No. (IMDG)	: 1263
UN-No.(ADN)	: 1263

### 14.2. UN proper shipping name

Proper Shipping Name	: PAINT / PAINT RELATED MATERIAL
Transport document description	: UN 1263 PAINT / PAINT RELATED MATERIAL, 3, III, (D/E)

### 14.3. Transport hazard class(es)

Class (UN)	: 3
Classification code (UN)	: F1
Class (IATA)	: 3
Class (IMDG)	: 3
Class (ADN)	: 3
Hazard labels (UN)	: 3



### 14.4. Packing group

Packing group (UN) : III

### 14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : No

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30

Classification code (UN) : F1

Orange plates :



Special provision (ADR) : 163, 650, 640E

Transport category (ADR) : 3

Tunnel restriction code : D/E

Limited quantities (ADR) : 5L

Excepted quantities (ADR) : E1

EAC code : •3YE

#### 14.6.2. Transport by sea

No additional information available

#### 14.6.3. Air transport

No additional information available

#### 14.6.4. Inland waterway transport

No additional information available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions

Contains no REACH candidate substance

Seveso Information :

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Abbreviations and acronyms : ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road). ATE: Acute Toxicity Estimated. CAS: Chemical Abstracts Service (division of the American Chemical Society). CLP: Classification, Labeling and Packaging. CMR: Carcinogène, Mutagène, Reprotoxique. CSA: Chemical Safety Assessment. CSR: Chemical Safety Report. DNEL: Derived No Effect Level (for human). EC50: Median Effective Concentration (required to induce a 50% effect). EINECS: European Inventory of Existing Commercial Chemical Substances. GHS: Globally Harmonized System of Classification and Labelling of Chemicals. IATA: International Air Transport Association. IMDG: International Maritime Code for Dangerous Goods. LC50: Lethal concentration, 50 percent. LD50: Lethal dose, 50 percent. PBT: Persistent, Bio accumulating and Toxic. PNEC: Predicted No Effect Concentration (for environment). REACH: Registration, Evaluation and Authorisation of Chemical substances. RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail). SVHC: Substances of Very High Concern. vPvB: very Persistent, very Bio accumulating.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. REACH Disclaimer:  
This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

### Full text of R-, H- and EUH-phrases::

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
R10	Flammable
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
N	Dangerous for the environment
Xn	Harmful

### SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*