



UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 24-10-21 Revision date: 20-09-21 Supersedes version of: 28-06-18 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : UV resistant varnish satin
Product code : 981

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Varnish

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664
Nijendal 36
3972 KC Driebergen Rijsenburg
Nederland
T 0031 343 518 224 - F 0031 343 516 342
info@oldholland.com - www.oldholland.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
Netherlands	Nationaal Vergiftigingen Informatie Centrum	Huispostnummer B.00.118 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Skin corrosion/irritation, Category 2 H315
Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Repeated exposure, Category 1 H372
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways. Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness.

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%), Hydrocarbons, C9, aromatics, reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
- : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective gloves, protective clothing.
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P391 - Collect spillage.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) substance with a Community workplace exposure limit	CAS-No.: 64742-82-1 EC-No.: 265-185-4 EC Index-No.: 649-330-00-2 REACH-no: 01-2119458049-33	< 70	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Muta. Not classified Carc. Not classified STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9, aromatics	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	15 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	CAS-No.: 104810-47-1, 104810-48-2 EC-No.: 400-830-7 EC Index-No.: 607-176-00-3 REACH-no: 01-0000015075-76	3 – 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
ethanol; ethyl alcohol substance with national workplace exposure limit(s) (NL)	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	0,25 – 2	Flam. Liq. 2, H225
acetone; propan-2-one; propanone substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	0,01 – 0,25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
methanol substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	0,01 – 0,25	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

Specific concentration limits:

Name	Product identifier	Specific concentration limits
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	(3 \leq C < 10) STOT SE 2, H371 (10 \leq C < 100) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand. Immediately call a POISON CENTER or doctor.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand. Foam. Dry powder. Carbon dioxide. Water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: For further information, refer to section 10 : "Stability and Reactivity".

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent fire fighting water from entering the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Do not breathe vapours, mist, spray.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container for disposal. Notify authorities if product enters sewers or public waters.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Concerning personal protective equipment to use, see item 8. Provide good ventilation in process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe vapours, mist, spray. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Explosion-free electrical equipment and lighting with earth. Ground/bond container and receiving equipment.
- Storage conditions : Keep only in the original container in a cool well ventilated place. Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids. Strong oxidation agent.
- Heat and ignition sources : Keep away from heat and direct sunlight. Ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	White spirit Type 1
IOEL TWA	116 mg/m ³
IOEL TWA [ppm]	20 ppm
IOEL STEL	290 mg/m ³
IOEL STEL [ppm]	50 ppm
Remark	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations
acetone; propan-2-one; propanone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
IOEL TWA [ppm]	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands - Occupational Exposure Limits	
Local name	Aceton
TGG-8u (OEL TWA)	1210 mg/m ³

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

acetone; propan-2-one; propanone (67-64-1)	
TGG-15min (OEL STEL)	2420 mg/m ³
Regulatory reference	Arbeidsomstandighedenregeling 2021
ethanol; ethyl alcohol (64-17-5)	
Netherlands - Occupational Exposure Limits	
Local name	Ethanol
TGG-8u (OEL TWA)	260 mg/m ³
TGG-15min (OEL STEL)	1900 mg/m ³
Remark	Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021
methanol (67-56-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methanol
IOEL TWA	260 mg/m ³
IOEL TWA [ppm]	200 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Netherlands - Occupational Exposure Limits	
Local name	Methanol
TGG-8u (OEL TWA)	133 mg/m ³
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Approved respirator.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses. EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 369; EN 465

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent)

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR), Polyvinylchloride (PVC)	6 (> 480 minutes)	≥0.11		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

Wear respiratory protection. EN 143

Respiratory protection			
Device	Filter type	Condition	Standard
Approved respirator	Type P1	Vapour protection, Protection for Liquid particles	EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Upper explosive limit (UEL)	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use. Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Keep away from heat and direct sunlight. Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong bases. Strong acids. Strong oxidation agent.

10.6. Hazardous decomposition products

Combustion generates: Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ethanol; ethyl alcohol (64-17-5)	
LD50 oral rat	6200 mg/kg
LD50 dermal rabbit	20000 mg/kg
LC50 Inhalation - Rat (Vapours)	95,6 mg/l/4h
Hydrocarbons, C9, aromatics (64742-95-6)	
LD50 oral rat	3592 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)	
STOT-single exposure	May cause drowsiness or dizziness.
acetone; propan-2-one; propanone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
Hydrocarbons, C9, aromatics (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)	
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Other information : Risk of aspiration pneumonia

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) (64742-82-1)	
EC50 - Crustacea [1]	7,8 g/l
EC50 - Other aquatic organisms [1]	3,59 g/l
ethanol; ethyl alcohol (64-17-5)	
LC50 - Fish [1]	8140 mg/l 48 h
EC50 - Crustacea [1]	9268 – 14221 mg/l 48 h
EC50 - Crustacea [2]	65 mg/l 72 h
ErC50 algae	1450 mg/l 8 d
Hydrocarbons, C9, aromatics (64742-95-6)	
LC50 - Fish [1]	9,2 mg/l
EC50 - Crustacea [1]	3,2 mg/l
ErC50 algae	2,6 – 2,9 mg/l
NOEC chronic fish	1,23 mg/l
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1, 104810-48-2)	
LC50 - Fish [1]	2,8 mg/l
EC50 - Crustacea [1]	4 mg/l
ErC50 algae	> 9 mg/l

12.2. Persistence and degradability

UV resistant varnish satin	
Persistence and degradability	Not established.
ethanol; ethyl alcohol (64-17-5)	
Biochemical oxygen demand (BOD)	0,9 – 1,67 g O ₂ /g substance
BOD (% of ThOD)	94 % ThOD

12.3. Bioaccumulative potential

UV resistant varnish satin	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

UV resistant varnish satin	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Endocrine disrupting properties

No additional information available

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
 Additional information : Handle empty containers with care because residual vapours are flammable. Empty containers should be taken for recycle, recovery or waste in accordance with local regulation. Flammable vapours may accumulate in the container.
 Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT / PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%))	PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%))	Paint (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%))	PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%))	PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%))
Transport document description				
UN 1263 PAINT / PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)), 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)), 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)), 3, II, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (CONTAINS ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (2-25%)), 3, II, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				


UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640D, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP8, TP28
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	: 
Tunnel restriction code (ADR)	: D/E

Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.
MFAG-No	: 127;128

Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 640C, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E2
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 640C, 650

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP8, TP28
Tank codes for RID tanks (RID)	: L1.5BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(a)	UV resistant varnish satin ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) ; acetone; propan-2-one; propanone ; ethanol; ethyl alcohol ; methanol ; Hydrocarbons, C9, aromatics
3(b)	UV resistant varnish satin ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) ; acetone; propan-2-one; propanone ; methanol ; Hydrocarbons, C9, aromatics ; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
3(c)	UV resistant varnish satin ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) ; Hydrocarbons, C9, aromatics ; reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
40.	UV resistant varnish satin ; Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) ; acetone; propan-2-one; propanone ; ethanol; ethyl alcohol ; methanol ; Hydrocarbons, C9, aromatics
69.	methanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-05/list_of_competent_authorities_and_national_contact_points_en.pdf

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Directive 2012/18/EU (SEVESO III)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5a FLAMMABLE LIQUIDS — Flammable liquids, Category 1, or — Flammable liquids Category 2 or 3 maintained at a temperature above their boiling point, or — Other liquids with a flash point ≤ 60 °C, maintained at a temperature above their boiling point	10	50
P5b FLAMMABLE LIQUIDS — Flammable liquids Category 2 or 3 where particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, or — Other liquids with a flash point ≤ 60 °C where particular processing conditions, such as high pressure or high temperature, may create major-accident hazards	50	200
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

Netherlands

SZW-lijst van kankerverwekkende stoffen	: Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%), ethanol; ethyl alcohol are listed
SZW-lijst van mutagene stoffen	: Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromatic compounds (16.3%) is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: ethanol; ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: ethanol; ethyl alcohol is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: ethanol; ethyl alcohol is listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Indication of changes	Added	
	Revision date	Modified	
	Supersedes	Modified	
	SDS EU format	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.2	Hazard statements (CLP)	Modified	
2.2	Precautionary statements (CLP)	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures general	Modified	
4.2	Symptoms/effects after skin contact	Modified	

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
5.1	Suitable extinguishing media	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
5.3	Protection during firefighting	Modified	
5.3	Firefighting instructions	Added	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Added	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Methods for cleaning up	Modified	
6.4	Reference to other sections (8, 13)	Modified	
7.1	Hygiene measures	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Storage conditions	Modified	
8.2	Other information	Modified	
8.2	Personal protective equipment	Modified	
8.2	Respiratory protection	Modified	
8.2	Skin and body protection	Modified	
10.1	Reactivity	Modified	
10.3	Possibility of hazardous reactions	Modified	
10.4	Conditions to avoid	Modified	
12.2	Persistence and degradability	Added	
12.3	Bioaccumulative potential	Added	
13.1	Additional information	Modified	
13.1	Waste disposal recommendations	Added	
15.1	REACH Annex XVII	Added	
16	Abbreviations and acronyms	Modified	
16	Data sources	Modified	

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CAS	CAS (Chemical Abstracts Service) number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	CMR: Carcinogen, Mutagen, Reprotoxisch
	CSA: Chemical Safety Assessment
	CSR: Chemical Safety Report
DNEL	Derived-No Effect Level

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
	EC50: Median Effective Concentration (required to induce a 50% effect)
	EINECS: European Inventory of Existing Commercial Chemical Substances
	GHS: Globally Harmonized System of Classification and Labelling of Chemicals
	IATA: International Air Transport Association
	IMDG: International Maritime Code for Dangerous Goods
	LC50: Lethal concentration, 50 percent
	LD50: Lethal dose, 50 percent
PBT	Persistent Bioaccumulative Toxic
	PNEC: Predicted No Effect Concentration (for environment)
	REACH: Registration, Evaluation and Authorisation of Chemical substances
	RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
	SVHC: Substances of Very High Concern
vPvB	Very Persistent and Very Bioaccumulative
SDS	Safety Data Sheet
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
LC50	Median lethal concentration
LD50	Median lethal dose
CAS	CAS (Chemical Abstracts Service) number
	EG-nr.: EINECS- en ELINCS-number
	EINECS: European Inventory of Existing Commercial Substances
	OEL: Occupational Exposure Limit

Data sources

: ECHA (European Chemicals Agency). according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878.

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. Not classified	Carcinogenicity Not classified
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Muta. Not classified	Germ cell mutagenicity Not classified
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	Calculation method
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method

UV resistant varnish satin

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Asp. Tox. 1	H304	Expert judgment
Aquatic Chronic 2	H411	Calculation method

The classification complies with : ATP 8

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)797676006 | info@chemprosbv.nl