



# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 31-1-2014 Revision date: 10-4-2026 Supersedes version of: 31-12-2024 Version: 6.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Oil Painting Medium Quick Drying  
UFI : F8AR-C749-E991-4374  
Product code : Z.V1108  
Type of product : Solvents

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Industrial use, Professional use  
Use of the substance/mixture : Medium  
Function or use category : Solvents

#### 1.3. Details of the supplier of the safety data sheet

Old Holland Classic Colours Since 1664  
Nijendal 36  
3972 KC Driebergen Rijsenburg  
Nederland  
T 0031 343 518 224, F 0031 343 516 342  
[info@oldholland.com](mailto:info@oldholland.com), [www.oldholland.com](http://www.oldholland.com)

#### 1.4. Emergency telephone number

Country/Area	Organisation	Emergency number
Netherlands	Nationaal Vergiftigingen Informatie Centrum (NVIC). Huispostnummer Q03.2.315. Postbus 85500 3508 GA Utrecht.	+31 88 755 80 00 Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
Acute toxicity (oral), Category 4 H302  
Skin corrosion/irritation, Category 2 H315  
Serious eye damage/eye irritation, Category 2 H319  
Skin sensitisation, Category 1 H317  
Specific target organ toxicity – Single exposure, Category 3, H336  
Narcosis  
Specific target organ toxicity – Repeated exposure, Category 1 H372  
Aspiration hazard, Category 1 H304  
Hazardous to the aquatic environment – Chronic Hazard, H411  
Category 2

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs (central nervous system) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

- : Danger
- : turpentine, oil; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; 1,2,4-trimethylbenzene
- : H226 - Flammable liquid and vapour.  
H302 - Harmful if swallowed.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H372 - Causes damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, eye protection, respiratory protection.  
P301+P310+P331 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP]
turpentine, oil	CAS-No.: 8006-64-2 EC-No.: 232-350-7 EC Index-No.: 650-002-00-6 REACH-no: 01-2119553060-53	50 – 70	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	EC-No.: 919-446-0 REACH-no: 01-2119458049-33	20 – 30	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	10 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
1,2,4-trimethylbenzene substance with national workplace exposure limit(s) (NL); substance with a Community workplace exposure limit	CAS-No.: 95-63-6 EC-No.: 202-436-9 EC Index-No.: 601-043-00-3 REACH-no: 01-2119472135-42	< 2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:dust,mist), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Octane and isomers	-	< 0,25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove contaminated clothes. Wash skin with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.  
Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : Risk of lung oedema. Harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Sand. Dry powder. Foam. Carbon dioxide. Water spray.  
Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.  
Explosion hazard : May form flammable/explosive vapour-air mixture.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon oxides (CO, CO<sub>2</sub>).

### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Evacuate unnecessary personnel. Do not breathe vapours, mist.

#### For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.  
Methods for cleaning up : Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container for disposal.  
Other information : Dispose of materials or solid residues at an authorized site.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use explosion-proof equipment. Ground/bond container and receiving equipment. Flammable vapours may accumulate in the container. Provide good ventilation in process area to prevent formation of vapour. Do not breathe vapours, mist. Avoid contact with skin and eyes. Wear personal protective equipment. Concerning personal protective equipment to use, see item 8.
- Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Keep only in the original container in a cool well ventilated place. Keep container tightly closed. Store locked up.
- Incompatible products : Strong bases. Strong acids. Strong oxidizing agents.
- Heat and ignition sources : Keep away from heat and direct sunlight. ignition sources.
- Packaging materials : Always store product in container of same material as original container.

### 7.3. Specific end use(s)

Solvent.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

1,2,4-trimethylbenzene (95-63-6)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	1,2,4-Trimethylbenzene
IOEL TWA	100 mg/m <sup>3</sup>
	20 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	1,2,4-Trimethylbenzeen
TGG-8u (OEL TWA)	100 mg/m <sup>3</sup>
	20 ppm
TGG-15min (OEL STEL)	200 mg/m <sup>3</sup>
	40 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2026

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

#### Personal protection equipment

**Personal protective equipment:**

Protective clothing. Gloves. Safety glasses. Breathing equipment.

**Personal protective equipment symbol(s):**

#### Eye and face protection

**Eye protection:**

Safety glasses. DIN EN 166

#### Skin protection

**Skin and body protection:**

Wear suitable protective clothing. ISO 13688

**Hand protection:**

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Gloves	Polyvinylchloride (PVC), Nitrile rubber (NBR)	6 (> 480 minutes)	≥0.11		EN ISO 374

#### Respiratory protection

**Respiratory protection:**

In case of inadequate ventilation wear respiratory protection.

Respiratory protection			
Device	Filter type	Condition	Standard
Aerosol mask	Type A - High-boiling (>65 °C) organic compounds, Type P2	Vapour protection, Protection for Liquid particles	EN 149

#### Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

**Other information:**

Do not eat, drink or smoke when using this product. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable liquid and vapour.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Flammable vapour/air mixtures may be formed.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. Keep away from heat and direct sunlight.

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidation agent.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

#### Oil Painting Medium Quick Drying

ATE CLP (oral)	1000 mg/kg bodyweight
----------------	-----------------------

#### turpentine, oil (8006-64-2)

LD50 oral rat	500 mg/kg
LD50 dermal rat	1100 mg/kg
LC50 Inhalation - Rat	11 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### 1,2,4-trimethylbenzene (95-63-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### Octane and isomers

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard : May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### Other information

Potential adverse human health effects and symptoms : Harmful if swallowed. Harmful if inhaled.

Other information : Risk of aspiration pneumonia

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

#### Oil Painting Medium Quick Drying

Persistence and degradability	No data is available on the degradability of this product.
-------------------------------	--

#### turpentine, oil (8006-64-2)

Persistence and degradability	Inherently biodegradable.
-------------------------------	---------------------------

Biodegradation	52 % (28 days)
----------------	----------------

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Persistence and degradability	Readily biodegradable.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Persistence and degradability	Readily biodegradable.
1,2,4-trimethylbenzene (95-63-6)	
Persistence and degradability	Biodegradability in water: no data available.
Octane and isomers	
Persistence and degradability	Biodegradability in water: no data available.

### 12.3. Bioaccumulative potential

turpentine, oil (8006-64-2)	
Bioconcentration factor (BCF REACH)	407
Partition coefficient n-octanol/water (Log Pow)	4,38

### 12.4. Mobility in soil

turpentine, oil (8006-64-2)	
Mobility in soil	Low mobility (soil)

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Oil Painting Medium Quick Drying	
Other information	Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapours are flammable. Empty containers should be taken for recycle, recovery or waste in accordance with local regulation.  
Ecological waste information : Avoid release to the environment.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

HP Code

- : HP3 - "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
- HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
- HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
- HP13 - "Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs.
- HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
<b>14.2. UN proper shipping name</b>				
PAINT / PAINT RELATED MATERIAL (contains turpentine, oil)	PAINT RELATED MATERIAL (contains turpentine, oil)	Paint related material (contains turpentine, oil)	PAINT RELATED MATERIAL (contains turpentine, oil)	PAINT RELATED MATERIAL (contains turpentine, oil)
<b>Transport document description</b>				
UN 1263 PAINT / PAINT RELATED MATERIAL (contains turpentine, oil), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (contains turpentine, oil), 3, III	UN 1263 Paint related material (contains turpentine, oil), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (contains turpentine, oil), 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL (contains turpentine, oil), 3, III, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
<b>14.4. Packing group</b>				
III	III	III	III	III

# Oil Painting Medium Quick Drying



## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: No EmS-No. (Fire): F-E EmS-No. (Spillage): S-E	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
	: 
Tunnel restriction code (ADR)	: D/E

#### Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.
MFAG-No	: 127;128

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

#### Inland waterway transport

Classification code (ADN)	: F1
---------------------------	------

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

#### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Oil Painting Medium Quick Drying ; turpentine, oil ; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; 1,2,4-trimethylbenzene ; Octane and isomers	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	Oil Painting Medium Quick Drying ; turpentine, oil ; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; 1,2,4-trimethylbenzene ; Octane and isomers	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	Oil Painting Medium Quick Drying ; turpentine, oil ; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ; 1,2,4-trimethylbenzene ; Octane and isomers	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### National regulations

#### Netherlands

ABM category	: A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: turpentine, oil is listed
SZW-lijst van mutagene stoffen	: turpentine, oil is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
	Revision date	Modified
	Supersedes	Modified
1.1	UFI on SDS 1.1	Added
1.1	Product code	Modified
2.1	Adverse physicochemical, human health and environmental effects	Modified
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified
2.2	Extra phrases	Removed
2.2	Precautionary statements (CLP)	Modified
2.2	Hazard statements (CLP)	Modified
3	Composition/information on ingredients	Modified
4.1	First-aid measures general	Modified
4.1	First-aid measures after skin contact	Modified
4.1	First-aid measures after inhalation	Modified
4.1	First-aid measures after ingestion	Modified
4.1	First-aid measures after eye contact	Modified
4.2	Symptoms/effects after inhalation	Removed
4.2	Symptoms/effects after skin contact	Modified
5.1	Suitable extinguishing media	Modified
5.2	Hazardous decomposition products in case of fire	Modified
5.3	Firefighting instructions	Modified
5.3	Protection during firefighting	Modified
5.3	Other information	Removed
6.1	General measures	Removed
6.1	Emergency procedures	Modified
6.1	Protective equipment	Modified
6.1	Emergency procedures	Modified
6.2	Environmental precautions	Modified
6.3	Methods for cleaning up	Modified
6.3	For containment	Modified
6.4	Reference to other sections (8, 13)	Modified
7.1	Precautions for safe handling	Modified
7.1	Hygiene measures	Modified
7.2	Storage conditions	Modified
8.2	Skin and body protection	Modified

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
8.2	Respiratory protection	Modified
8.2	Eye protection	Modified
8.2	Personal protective equipment	Modified
8.2	Other information	Modified
9	Melting point	Removed
9	Solubility	Added
10.4	Conditions to avoid	Modified
10.6	Hazardous decomposition products	Modified
11	Adverse health effects caused by endocrine disrupting properties	Added
11.1	Additional information	Removed
11.1	Additional information	Removed
11.1	Additional information	Removed
11.1	Additional information	Removed
11.1	ATE CLP (dust,mist)	Removed
12.1	Ecology - general	Modified
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added
13.1	Additional information	Modified
13.1	Sewage disposal recommendations	Removed
13.1	Waste disposal recommendations	Modified
14	Proper Shipping Name (IATA)	Modified
14	Proper Shipping Name (IMDG)	Modified
14	Proper Shipping Name (RID)	Modified
14.2	Proper Shipping Name (ADR)	Modified
14.2	Proper Shipping Name (ADN)	Modified
15.1	REACH Annex XVII	Modified
16	Abbreviations and acronyms	Modified

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CAS	CAS (Chemical Abstracts Service) number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DNEL	Derived-No Effect Level
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
CAS	CAS (Chemical Abstracts Service) number

Data sources

: ECHA (European Chemicals Agency). Supplier's safety documents.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Other information

: **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number).

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

# Oil Painting Medium Quick Drying

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	Calculation method
Acute Tox. 4 (Oral)	H302	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method
Asp. Tox. 1	H304	Expert judgement
Aquatic Chronic 2	H411	Calculation method

The classification complies with : ATP 12

This Safety Data Sheet is compiled by: ChemPros B.V. | +31(0)858881927 | info@chemprosbv.nl